

1 Product identification code: <b>PWFLF</b>		
2. Type, batch, serial number or any other element allowing the identification of the construction product pursuant to Art.11, paragraph 4: <b>UNIBAR F</b> Date and production site and/or other identification data are printed on the packaging or on the Delivery Note		
3. Intended use(s) of the construction product, in accordance with the relevant harmonised technical specification, as provided by the manufacturer: <b>Breathable finish based on epoxy resins in aqueous dispersion</b>		
4. Name, registered trade name or registered trademark and address of the manufacturer pursuant to Art.11, paragraph 5:  <div style="text-align: center;"> <b>Winkler S.r.l.</b>  <b>Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy</b>  <b>Tel. +39 02/267.00.605</b>  <a href="mailto:info@winklerchimica.com">info@winklerchimica.com</a> <a href="http://www.winklerchimica.com">www.winklerchimica.com</a> </div>		
5. If applicable, name and address of the authorised representative whose mandate covers the tasks referred to in Art.12, paragraph 2:  <div style="text-align: center;"> <b>Not applicable</b> </div>		
6. System or systems of assessment and verification of the constancy of performance of the construction product referred to in Annex V  <div style="text-align: center;"> <b>System 4</b> </div>		
7. In the case of a declaration of performance concerning a construction product falling within the scope of a harmonised standard:  <div style="text-align: center;"> <b>No Obligation of the Notified Body</b> </div>		
8. In the case of a declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  <div style="text-align: center;"> <b>Not applicable</b> </div>		
9 <b>Declared performance:</b>		
<b>Essential Characteristics</b>	<b>Performance</b>	<b>Harmonised Technical Specification</b>
Wear resistance to rotating loads	≤ RWA10 (≤ 10cm <sup>3</sup> )	<b>UNI EN 13813</b> Materials for screeds
Impact resistance	≥ IR4 (≥ 20 N.m)	
Adhesion strength	B2.0 (≥ 2.0 N/mm <sup>2</sup> )	
Fire reaction	F	
Release of hazardous substances	See SDS	
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.		

Signed for and on behalf of the Manufacturer   Cologno Monzese, May 2023	Person responsible for the D.O.P. Luca Rossi  
---	--