

## USE FIELD

Product used to produce adhesive cement slurries for casting joints or for the packaging of cement mixtures with excellent workability, impermeability and great adhesion. It is used for restorations, repairs, plasters, smoothing, swimming pools, dams, floors, wear-resistant slabs, ramps, etc.

It can be used as an adhesion promoter on concrete before applying WINPLAN 370 and WINPLAN PRO screeds. In this case, the screeds must be applied using the "wet on wet" technique.

## SURFACE PREPARATION

Carefully clean the support to remove: dust, crumbly parts, foreign or non-sticking substances. Before applying the grout or the cement mix, wet the substrate until it is no longer absorbed and protect it for the first 24 hours, moistening if necessary, from direct sunlight and wind.

## PRECAUTIONS

Do not add additives.

Do not use if the container is damaged.

Do not add water if not suggested for the desired application.

Shake before using.

## APPLICATION

After shaking the product in its tank, add it to the mixing water.

## WARNINGS

Before applying the grout or the cement mix, wet the substrate until it is no longer absorbed and protect it for the first 24 hours, moistening if necessary, from direct sunlight and wind.

## CONSUMPTION

Liquid cement slurry: 2.5 parts of cement, 1 part of Adegum Latex, 1 part of water.

Rough cement slurry: 2.5 parts of cement, 2 parts of sand, 1 part of Adegum Latex, 1 part of water.

Mortars: 10% of the weight of the cement.

## PACKAGING

Bottles of 1 lt. Tanks of 5-10-20 lt.

## STORAGE

The product has 12 months stability if properly stored in a cool dry place.

Store at temperatures between + 5 ° C and + 35 ° C.

## PRECAUTIONS

For information about safety standards, user must refer to the most recent Safety Data Sheet, drawn up in accordance with current standards, containing physical, toxicological and other data relating to the product in use.

## ECOLOGY

Do not dispose the product and / or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about any possible disposal.

## TECHNICAL FEATURES

Look:	liquid
Colour:	white
Specific weight (g/cm <sup>3</sup> )	From $+1.05 \pm 0.02$ to $+20$ °C
Reaction to fire (Euroclass):	F
Dry residue (%):	about 28
pH of the mixture:	$9 \pm 1$
Elongation (%):	1000
Minimum film forming temperature:	$+5$ °C
Customs heading:	3209 10 00

Product meets with prescriptions of 2003/53/CE Directive.

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and update said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.