

# PRODUCT DATA SHEET

ITEM CODE: SEE DN  
ISSUE DATE: 26/04/2023  
REVIEW: NO. 1

## 2000 FAST PRIMER

### DESCRIPTION OF THE PRODUCT

Primer based on high-quality polymers and additives in water dispersion, with special fillers. Formulated by WINKLER Research & Development Laboratories.

### FIELDS OF USE

The product is designed to block oil migration from freshly applied bituminous membranes. This allows the immediate over-application of liquid protective coatings from the **2000 FAST** and **2000 PLUS B<sub>ROOF T2</sub>** ranges.

### SURFACE PREPARATION

Thoroughly clean the substrate to remove dust, loose or friable material, and any foreign or non-adherent substances.

Seal any raised edges or imperfections with **WINSEAL**.

### RECCOMENDATIONS

Do not add additives.

Do not use the product if the packaging is damaged.

Do not add water or solvents.

### WARNINGS

Ensure that the product is completely dry before over-laying.

Apply at temperatures between +5°C and +35°C.

### APPLICATION

The product is ready to use; stir briefly before application. Apply in a single coat on a clean, dry surface using a roller, brush, or airless pump.

Refer to the table below for the recommended waiting time before over-laying **2000 FAST PRIMER**.

# PRODUCT DATA SHEET

**TABLE 1 – DRYING TIME 2000 FAST PRIMER**

<b>WHEATHER CONDITIONS</b>	<b>OVER-APPLYING</b>
20°C up to 55% RH	3 h
15°C up to 55% RH	5 h
10°C up to 55% RH	8 h
5°C up to 55% RH	12 h

## **CONSUMPTION**

250 g/m<sup>2</sup> in one coat

## **PACKAGING**

10-20 kg buckets

## **STORAGE**

The product in its original and undamaged packaging, can be stored for up to 12 months. Store at temperatures between +5°C and 35 °C. The product is not frost-resistant.

## **SAFETY INSTRUCTIONS**

### **PRECAUTIONS**

For safety information, the user must refer to the latest Safety Data Sheet (SDS), prepared in accordance with applicable regulations. The SDS contains detailed information on the physical, toxicological, and safety characteristics of the product.

### **DISPOSAL AND ENVIRONMENTAL PRECAUTIONS**

Do not release the product or empty containers into the environment. For detailed disposal instructions, refer to the most recent Safety Data Sheet (SDS).

# PRODUCT DATA SHEET

## TECHNICAL FEATURES (average value)

FEATURES	STANDARD	RESULTS
Appearance	-	Liquid
Colour	-	Milky white
Specific gravity at 20°C	EN ISO 2811-1	1,15 ± 0,05 g/cm <sup>3</sup>
pH	UNI EN 8490-4	10 ±1
Brookfield viscosity at 20°C	UNI EN 8490	500 ± 100 cps

### DISCLAIMER AND LEGAL NOTICE – WINKLER

The information and instructions contained in this Technical Data Sheet are prepared on the basis of WINKLER's best technical and application knowledge and are provided for guidance only. However, since WINKLER cannot directly control site conditions or the execution of works, these indications are in no way binding on WINKLER.

The data provided do not exempt the purchaser from the responsibility of verifying, through practical tests and comprehensive applications, the suitability of the product for the intended use and of determining whether it is appropriate for the desired application; the user assumes all responsibility arising from its use. The customer is also responsible for verifying that this Technical Data Sheet is valid for the batch of product of interest and that it has not been superseded by later editions. The updated Technical Data Sheet is available on WINKLER's official website.

The contents of this Technical Data Sheet may be reproduced in other project documents, but the resulting document may under no circumstances replace or supplement the Technical Data Sheet in force at the time of application of the WINKLER product. Any alteration of the text or conditions contained in this Technical Data Sheet or derived from it releases WINKLER from any liability. WINKLER reserves the right to make technical changes of any kind to its products and/or Technical Data Sheets without notice. This revision cancels and replaces all previous ones.