

1 Product Unique Identification code: **PVFB**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: **2021 FIBER**

Date and production place and/or other identification data are printed on packaging or BoL

3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: **Coloured, fibre reinforced, water-based, elastomeric membrane**

4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5:

Winkler S.r.l.
Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy
Tel. +39 02/267.00.605
info@winklerchimica.com www.winklerchimica.com

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2):

Not relevant

6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V

System 3,4

7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

No obligation about notified Laboratory.

8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued:

Not relevant

9 **Declared performance**

Essential Characteristics	Test Method	Technical Specification	Test Result	UNI EN 1504-2 Concrete surface protection systems (MC-IR)
Water vapour permeability	EN ISO 7783 - 2	$s_d < 5 \text{ m}$	2,21m	
Capillary absorption	EN 1062 - 3	$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	0,01 kg/m ² xh ^{0.5}	
Adhesion strength by pull-off test	EN 1542	$\geq 2,0 \text{ N/mm}^2$	2,5 N/mm ²	
Adhesion after thermal compatibility with de-icing salt immersion	EN 13678 – 1 x 50 EN 13678 – 2 x 10	$\geq 2,0 \text{ N/mm}^2$	2,3 N/mm ²	
Adhesion after thermal compatibility without de-icing salt immersion	EN 13678 –3 x 20	$\geq 2,0 \text{ N/mm}^2$	2,3 N/mm ²	
Fire reaction	EN 13501-1	Declared	F	
Dangerous Substances Emission	See MSDS	See MSDS		

10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.

Signed for and on behalf of the Manufacturer

Management and Quality Supervisor
Luca Rossi

Cologno Monzese, 2025 December

