

1 Product Unique Identification code: **VBCM**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: **BOND CEMENT (C2 T E S2)**

Date and production place and/or other identification data are printed on packaging or Delivery note.

3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: **Two-component, waterproofing, cementitious adhesive, for both indoor and outdoor laying an overlapping flooring or ceramic coverings.**

4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5:

Winkler S.r.l.
Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia
Tel. +39 02/267.00.605 – Fax +39 02/267.00.621
info@winklerchimica.com www.winklerchimica.com

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2):

Not relevant

6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V

System 3 for water impermeability
System 4

7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

Water impermeability determined by the notified test Laboratory (n.0407) Istituto Giordano, based on tests on samples taken by the manufacturer, according to system 3, releasing the TEST REPORT N.323167 / 9012 / CPR

8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued :

Not relevant

9 **Declared performance**

Essential Characteristics	Essential Characteristics	Essential Characteristics
Tensile adhesive strenght:		UNI EN 14891 (CM 02 P)
- Initial	≥ 1.00 N/mm ²	
- After immersion in water	≥ 1.00 N/mm ²	
- After thermal aging	≥ 1.00 N/mm ²	
- After frosting-defrosting cycles	≥ 1.00 N/mm ²	
- After contact with lime water	≥ 1.00 N/mm ²	
Water impermeability	No break	
Crack bridging (at +23°C)	1.39 mm	
Crack bridging (at -5°C)	1.05 mm	
Crack bridging (at -20°C)	1.0 mm	
Release of hazardous substances	See MSDS	

10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.

Signed for and on behalf of the Manufacturer

Management and Quality Supervisor
Luca Rossi

Cologno Monzese, Giugno 2020

