

NATURE OF PRODUCT

Emulsifiable ecological release agent for wooden formworks, developed by the WINKLER Research & Development laboratories.

FILEDS OF USE

Product used for the removal of wooden formwork. Suitable for steam or natural maturation. It does not cause staining and guarantees painting and plastering without the risk of detachment.

SURFACES PREPARATION

Thoroughly clean the support to remove: dust, oils, greases, foreign or non-stick substances. The application must take place on a dry surface.

RECOMMENDATIONS

Do not add additives.

Do not use if the packaging is damaged.

WARNINGS

Make sure that the product is completely dried, before pouring. We recommend to apply the product at temperatures between + 5 ° C and + 35 ° C.

APPLICATION

Dilute the product with clean water in a ratio of 1: 5 to a maximum of 1:20. The emulsified product can be applied by roller, brush or by airless gun. When applied with a brush or roller, make an appropriate pressure until the homogeneous distribution is achieved over the entire surface, if applied by spray, blend several times in order to avoid sagging (if this happens, remove the material with a dry cloth).

CONSUMPTION

30-40ml of emulsion per m²

PACKAGING

5-20lt jerrycans.

STORAGE

The product, in its original packaging and stored in a dry and protected place has a stability of 12 months. Keep away from frost. Store at temperatures between + 5 ° C and + 35 ° C.

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

TECHNICAL DATA (average values)

PRODUCT FOR PROFESSIONALS

PRODUCT CHARACTERISTICS

Appearance:	-	-	Clear liquid
Color:	ASTM D 1500	-	4.0
Density at 15°C:	ASTM D 1298	kg/dm ³	0.905
5% pH in water:	ASTM E 70	-	7.5
Water dispersion:	-	-	Milky emulsion

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.