

## NATURE OF THE PRODUCT

Environmental-friendly, ready for use, form-release agent, developed by WINKLER Research & Development Laboratories.

## USE

DISARMO UNIVERSALE is a product intended for the release of prestressed and non concrete, subject to natural, accelerated or steam curing for wooden, metal, polystyrene, rubber and polyurethane formworks. It does not allow any barrier effect, which allows painting, plastering, or any other covering without subsequent detachments.

## PREPARATION OF SURFACES

Carefully clean the base in order to remove: dust, oil, grease and any foreign bodies or substances impeding adhesion. Apply on a dry surface.

## RECOMMENDATIONS

Do not use if the container is damaged.  
Do not add water.

## WARNINGS

Before pouring, make sure that the product is completely dry.  
We recommend applying at temperatures between +5°C and +35°C.

## APPLICATION

The product is ready for use and can be applied using a roller, hand brush or an airless gun. In case of new formworks, particularly absorbent or restored due to rust, double application is recommended. Wait for the evaporation of the water and the appearance of the oily surface before the installation.

## CONSUMPTION

20-25 g/m<sup>2</sup>  
About 30 g/m<sup>2</sup> with double applicazione

## PACKAGING

5-20 litre jerrycans.

## STORAGE

If the product is stored in its unopened original packaging in a dry and protected place, shelf-life is 12 months. Not frost-proof. Store at temperatures between +5°C and +35°C.

## SAFETY STANDARDS

### CAUTION

For information about safety standards, users must refer to the most recent Safety Sheet drafted in compliance with currently applicable Safety Standards, containing physical, toxicological and other data about the product used.

### ECOLOGY

Dispose of the product and/or empty packaging in appropriate sites. For further information about waste disposal, see the most recent Safety Sheet.

## TECHNICAL DATA (average values)

### PRODUCT FOR PROFESSIONALS

### PRODUCT DATA

Appearance:	liquid
Colour:	white
Density at 15° C:	0.97 g/cm <sup>3</sup>
Yield:	50m <sup>2</sup> /lt
Flash point C.O.C.	non-inflammable
Biodegradability:	90%

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.