



Declaration of Performance

nr. 015CPR01072013

Rev. 00

Decree 305/2011

Page 1 of 1

1 Product Unique Identification code: **VJXB VJXG**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: **ROYAL EXTRA (C2 T E)**

Date and production place and/or other identification data are printed on packaging or BoL

3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: **Cement-based tile adhesive improved with additional features characterized by reduced slip and prolonged open time for collocation of ceramic and stone tiles or coverings.**

4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5:

Winkler S.r.l.
Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy
Tel. +39 02/267.00.605 – Fax +39 02/267.00.621
info@winklerchimica.com www.winklerchimica.com

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2):

Not relevant

6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V

System 3

7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

Product – Type determined by the notified test laboratory Istituto Masini, based on tests on samples taken by the manufacturer, according to System 3, releasing the TEST REPORT nr. 917-2008

8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued :

Not relevant

9 **Declared Performance:**

Essential Characteristics	Performances	Harmonised Technical Specification
Initial adhesion traction	1,30 N/mm ²	UNI EN 12004:2007
Adhesion after thermal cycles	1,05 N/mm ²	
Adhesion after water immersion	1,35 N/mm ²	
Adhesion after frost-defrost cycles	1,01 N/mm ²	
Fire reaction	A1	
Durability	NPD	
Dangerous Substances Emission	See MSDS	

10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.

Signed for and on behalf of the Manufacturer

Management and Quality Supervisor
Luca Rossi

Cologno Monzese 2019 May 24th