

DESCRIPTION

Eco-friendly, transpiring, anti-moss powder based paint. Formulated by WINKLER Research & Development laboratories.

USE

Product for internal and external use, composed of special substances to prevent or eliminate mustiness and efflorescence. It can be applied on places as baths, kitchen...where moisture is high, or as finishing restoring cycle for counter humidity. SANAPITT applied on walls results smooth and gives a light glossy look to the structure.

SURFACES PREPARATION

Accurately clean the support for removing: dust, crumbly parts, foreign or bonding-proof matters. Fill in any eventual cracks on the surface.

APPLICATION

Mix well until getting a perfectly homogeneous compound, free from lumps. Let it rest for about 10 minutes, then apply it by roller or brush. Wait at least 3 hours between the first and the second hand. The product can be colored by using a normal coloring paste, available in every paint factory.

WARNING

Do not add any cement nor additive.

Do not use if the packaging is damaged.

Apply at temperatures between +5°C and +35°C. mix only the needed quantity of product, to avoid waste.

CONSUMPTION

75g/m²

Recommended mixing ratio: SANAPITT kg. 1
WATER lt. 0,8

PACKAGING

3 kg bags – 8 bags per box

10 kg bags

STORAGE

The product in its undamaged packaging can be stored for 24 months. Please store it in a protect and dry place, at temperatures between +5°C and +35°C.

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not dispose the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

TECHNICAL FEATURES

Appearance:	Powder
Colour:	White
Density at 20°C:	0.7 g/cm ³
Consumption if not diluted in water:	110g/m ² per coat
Dry time at 20°C:	8-10 hours
Vapour permeability	About 200 g/m ² /24h (DIN 18363)

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.