

SKERMO ANTISCRITTA

DESCRIPTION OF THE PRODUCT

Water-based, anti-graffiti protective coating. Formulated by WINKLER Research & Development Laboratories.

FIELDS OF USE

Specially formulated to provide long-lasting protection against paints, marker pens, and dirt on concrete, natural stone, brick, or plaster surfaces. It also imparts a water-repellent finish to the substrate.

SURFACE PREPARATION

Thoroughly clean the surface to remove dust, oil, grease, and any foreign materials or substances that may impair adhesion.

WARNING

Do not add cement or any additives.
Do not use the product if the packaging is damaged.
Do not add solvents unless specifically required for the application.

PRECAUTIONS

Fill in existing cracks before application. Do not apply if rain is imminent, on heated surfaces, or on surfaces directly exposed to UV rays. Protect the product from water, rain, and snow during the first 24 hours after application. Apply at temperatures between +5°C and +35°C.

APPLICATION

The product is ready to use and can be applied with a brush, roller, or a low-pressure spray gun. It is recommended to apply at least two coats, "wet-on-wet".

To remove graffiti from surfaces treated with **SKERMO ANTISCRITTA**, a pressure washer or hot water rubbed with a rough sponge is sufficient. **SKERMO ANTISCRITTA** must be reapplied after each cleaning.

CONSUMPTION

150-180 ml/m² in at least two coats

PACKAGING

5-20 L buckets

STORAGE

The product in its original and undamaged packaging, can be stored for up to 12 months. Store at temperatures between +5°C and 35 °C. The product is not frost-resistant.

SAFETY INSTRUCTIONS

PRECAUTIONS

For safety information, the user must refer to the latest Safety Data Sheet (SDS), prepared in accordance with applicable regulations. The SDS contains detailed information on the physical, toxicological, and safety characteristics of the product.

DISPOSAL AND ENVIRONMENTAL PRECAUTIONS

Do not release the product or empty containers into the environment. For detailed disposal instructions, refer to the most recent Safety Data Sheet (SDS).

TECHNICAL FEATURES (average value)

FEATURES	RESULTS
Appearance	Liquid
Colour	Milky
Dust-free drying time:	25-30 minutes at +20°C
Drying time:	1 hour at +20°C
Specific weight	0.99 g/cm ³
pH	11

The product complies with the requirements of Directive 2003/53/EC.

PRODUCT FOR PROFESSIONAL USE ONLY

DISCLAIMER AND LEGAL NOTICE - WINKLER

The information and instructions contained in this Technical Data Sheet are prepared on the basis of WINKLER's best technical and application knowledge and are provided for guidance only. However, since WINKLER cannot directly control site conditions or the execution of works, these indications are in no way binding on WINKLER.

The data provided do not exempt the purchaser from the responsibility of verifying, through practical tests and comprehensive applications, the suitability of the product for the intended use and of determining whether it is appropriate for the desired application; the user assumes all responsibility arising from its use. The customer is also responsible for verifying that this Technical Data Sheet is valid for the batch of product of interest and that it has not been superseded by later editions. The updated Technical Data Sheet is available on WINKLER's official website.

The contents of this Technical Data Sheet may be reproduced in other project documents, but the resulting document may under no circumstances replace or supplement the Technical Data Sheet in force at the time of application of the WINKLER product. Any alteration of the text or conditions contained in this Technical Data Sheet or derived from it releases WINKLER from any liability. WINKLER reserves the right to make technical changes of any kind to its products and/or Technical Data Sheets without notice. This revision cancels and replaces all previous ones.