

1 Product Unique Identification code: <b>PJF30000</b>		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: <b>WF03 - WINTOSAN</b> Date and production place and/or other identification data are printed on packaging or BoL		
3.Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: <b>Dehumidifying and breathable plaster</b>		
4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5:  <b>Winkler S.r.l.</b> <b>Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy</b> <b>Tel. +39 02/267.00.605 – Fax +39 02/267.00.621</b> <b><a href="mailto:info@winklerchimica.com">info@winklerchimica.com</a> <a href="http://www.winklerchimica.com">www.winklerchimica.com</a></b>		
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (2): <b>Not relevant</b>		
6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V <b>System 4</b>		
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: <b>No obligation about notified Laboratory.</b>		
8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : <b>Not relevant</b>		
<b>9 Declared Performance:</b>		
<b>Essential Characteristics</b>	<b>Performances</b>	<b>Harmonised Technical Specification</b>
Compressive resistance	14.5 N/mm <sup>2</sup> (cat. CS II)	<b>UNI EN 998-1</b> Restoration mortar (R)
Adhesion	≥ 0.4 N/mm <sup>2</sup> (Break type: B)	
Capillarity water absorption	≥ 3.1 Kg/m <sup>3</sup> (water infiltration ≤ 5mm)	
Water vapor permeability	≤ 15	
Thermal conductivity λ	0.70 W/m.K	
Fire reaction	A 1	
Dangerous Substances Emission	See MSDS	
10. The performance of the product identified at points 1 and 2 is in conformità with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.		

Signed for and on behalf of the Manufacturer	Management and Quality Supervisor Luca Rossi
Cologno Monzese, December 2020	