

SHORT INFORMATION

Cold self-adhesive reparation tape for universal use. For sealing, connecting and insulating:

- Gutter joints, skylights, chimneys, walls, ridge formations, drain pipes, aerial junctions, metal and synthetic material connections, joints, cracks, etc.
- Adhesion to brickwork, plaster, concrete, wood, metal, steel, glass, zinc and aluminium

MATERIAL

Aluminum sandwich foil with a self-adhesive bitumen-elastomer layer.

COLOURS

- Aluminium
- Lead

Additional colours on request

PRODUCT ADVANTAGES

- Special protective foil (prevents capillary action)
- Waterproof
- UV-resistant
- Simple, easy and cheap application

AVAILABILITY

On rolls, with a self-adhesive bitumen-elastomer layer (thickness 1.2 mm).

DIMENSIONS/SIZES

Roll length: 10 m.

Order No. Width x Thickness in mm.	Rolls per Carton	Content per Carton in m
50 x 1.2	6	60
75 x 1.2	4	40
100 x 1.2	3	30
150 x 1.2	2	20
200 x 1.2	1	10
300 x 1.2	1	10

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

TECHNICAL DATA

	DIN	Classification
Building material class	4102	B2 (normal flammability)
Temperature resistance		-30°C to +80°C
Application temperature		+5°C to +30°C
Shelf life Bitumen Tape Alu		9 months in unopened, original packaging
Shelf life Butyl- & Bitumen-Primer		12 months
Storage temperature		+10°C to +25°C

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.