

DESCRIPTION OF THE PRODUCT

Insulating and consolidating primer based on polymers in water dispersion. This product is totally free from organic compounds, so it can be considered as environmental friendly. It has been formulated by WINKLER Research & development Laboratories.

USE FIELD

Thanks to its special formulation, which allows an high permeation into supports, this product is an excellent dust cover/strengthening for concrete, screeds, magnesite panels, walls and ceilings, before the application of water paints and smoothing mortar. Furthermore, it can be used as an insulator of plaster and anhydrite substrates.

PREPARATION OF SURFACES

Ensure that the application surfaces are free from greases and salts, clean and free from brittle parts, apply on dry surfaces.

APPLICATION

The product is ready to use and can be applied by roller, brush, large brush and airless gun. Before overcoating, ensure that the fixative is completely absorbed by the surface.

WARNING

Do not add any additives .

Do not add water nor solvents.

Do not apply the product on frost surfaces or subject to night chill or with rainy weather. Apply the product at temperatures between +5°C and +35°C

CONSUMPTION

120-130 g/m² in one coat.

PACKAGING

5-10-20 kgs cans.

STORAGE

The product in its undamaged packaging and in a dry and protected place can be stored for 12 months. Please store it at temperatures between +5 and 35°C. No frost-proof.

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

TECHNICAL FEATURES

PRODUCT FOR PROFESSIONAL ONLY

Aspect:	liquid
Color:	opalescent white
Specific weight at 20°C (g/cm ³):	1,0
Dust dry drying at 20°C (minutes):	60 - 90
Solid content(%):	11
pH:	8,5 ± 0,5
cPs Brookfield viscosity:	15

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.