

## DESCRIPTION

Closed cell non-crosslinked polyethylene foam backer rod.

## FIELDS OF USE

WINJOINT FOAM is used as a non-adhesive filling, to correctly size the depth of the expansion joints (creation of the "third wall" or bottom of the joint), before being filled with WINJOINT SEAL, polyurethane sealant. It is a flexible and easy to apply curb, it also has good resistance to many chemicals.

## SURFACE PREPARATION

Substrate must be free from crumbly, foreign or non-stick substances. Apply the product on dry surface.

## WARNING

Do not expose to direct sunlight for a long time (max 4 hours).

## APPLICATION

The diameter of the WINJOINT FOAM should be about 25% larger than the width of the joint, to allow a stable positioning of the profile. Use a rounded tipped tool (without sharp and pointed edges), able to cross the width of the joint, up to the desired depth.

## DIMENSIONS

Diameter(mm)	Lenght/box (m)
10	550
15	550
20	350
25	200
30	160

## STORAGE

Store in a dry place, protected by sun rays.

## SAFETY INSTRUCTIONS

### PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

### ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

## TECHNICAL DATA (average values)

### PRODUCT FOR PROFESSIONALS

	Test method	Value
Water absorption (g/cc)	ASTM C 1016 – Proc. B	< 0.03
Density (Kg/m <sup>3</sup> )	ASTM D 1622	25±5
Compression recovery (%)	ASTM D 5249	>90
Compression deflection (kPa)	ASTM D 5249	>20.5
Working temperatures (°C)	-	From -40 to +80
Tensile Strenght (kPa)	ASTM D1632	>200

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and update said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.