

1 Product Unique Identification code: VWSM		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: WINSTUCCO FLEX MEDIUM Date and production place and/or other identification data are printed on packaging or Delivery note.		
3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: Waterproofing and flexible cementitious grout, for grout-lines from 2mm to 12 mm wide.		
4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: <p style="text-align: center;">Winkler S.r.l. Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 info@winklerchimica.com www.winklerchimica.com</p>		
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2): Not relevant		
6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V System 4		
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: No obligation about notified Laboratory.		
8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : Not relevant		
9 Declared performance		
Essential Characteristics	Essential Characteristics	Essential Characteristics
Abrasion resistance	$\leq 2000\text{mm}^3$	UNI EN 13888 Improved cementitious grout with additional characteristic of reduced water absorption (CG 2 W)
Flexural resistance after dry storage	$\geq 2.5 \text{ N/mm}^2$	
Flexural resistance after freeze-thaw cycles	$\geq 2.5 \text{ N/mm}^2$	
Compressive resistance after dry storage	$\geq 15 \text{ N/mm}^2$	
Compressive resistance after freeze-thaw cycles	$\geq 15 \text{ N/mm}^2$	
Shrinkage	$\leq 3.0\text{mm/m}$	
Reduced water absorption after 30 minutes	$\leq 2 \text{ days}$	
Reduced water absorption after 240 minutes	$\leq 5 \text{ days}$	
10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.		

Signed for and on behalf of the Manufacturer	Management and Quality Supervisor Luca Rossi
Cologno Monzese, 2020 September	