



# Declaration of Performance

nr. 019CPR01072013

Rev. 00

Decree 305/2011

Page 1 of 1

1 Product Unique Identification code: <b>VJMA</b>		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Art.11, clause 4: <b>WMA WINFORCE</b> Date and production place and/or other identification data are printed on packaging or BoL		
3. Intended or expected uses of the construction product, according with the applicable harmonized technical specification as conceived by the manufacturer: <b>NON SHRINK CEMENT MORTAR</b>		
4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Art.11, clause 5: <p style="text-align: center;"><b>Winkler S.r.l.</b> <b>Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italy</b> <b>Tel. +39 02/267.00.605 – Fax +39 02/267.00.621</b> <a href="mailto:info@winklerchimica.com">info@winklerchimica.com</a> <a href="http://www.winklerchimica.com">www.winklerchimica.com</a></p>		
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Art.12 (paragraph 2): <p style="text-align: center;"><b>Not relevant</b></p>		
6. System or more systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in Annex V <p style="text-align: center;"><b>System 4</b></p>		
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: <p style="text-align: center;"><b>No obligation about notified Laboratory.</b></p>		
8. In case of declaration of performance concerning a construction product for which European Technical Assessment (ETA) has been issued : <p style="text-align: center;"><b>Not relevant</b></p>		
9 <b>Declared Performance:</b>		
<b>Essential Characteristics</b>	<b>Performances</b>	<b>Harmonised Technical Specification</b>
Fire reaction	Euroclass A1	<b>UNI EN 1504-6:2006</b>
Adhesion on smooth steel	≥4.5 MPa	
Adhesion on concrete	≥ 7.0 MPa	
Slipping off resistance	Passed	
Chloride Ions content	≤ 0.05%	
Dangerous Substances Emission	See MSDS	
10. The performance of the product identified at points 1 and 2 is in conformity with the declared performance at point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified at point 4.		

Signed for and on behalf of the Manufacturer

Management and Quality Supervisor  
Luca Rossi

Cologno Monzese 2019 May 24th