

PRODUCT DATA SHEET

WINCOURT TC

ITEM CODE: SEE DN
ISSUE DATE: 11/06/2026
REVIEW: 01

PRODUCT DESCRIPTION

Protective water-based coating made with the highest-quality polymers and copolymers. The product is completely free of organic solvents and therefore has a very low environmental impact. It has been formulated in the **Research & Development laboratories of Winkler**.

FIELDS OF USE

It can be applied to concrete substrates, screeds, concrete and cement-based surfaces in general, asphalt (at least 30 days after application), and fiber cement. It offers exceptional resistance to pedestrian traffic, UV radiation, high and low temperatures, as well as harsh weather conditions.

SURFACE PREPARATION

Carefully clean the substrate to remove dust, loose or friable material, and any foreign or release agents. The product should be applied only to a dry surface. Although the product can tolerate a moisture content between 3% and 5%, it is recommended to check the substrate for any hidden or excessive moisture to prevent vapor pressure build-up and related issues.

RECCOMENDATIONS

Do not add cement or additives.
Do not use if the container is damaged.
Do not add water and/or solvents.

WARNINGS

The product must be applied under environmental conditions that ensure complete drying in the shortest possible time. Therefore, do not apply the product on frozen surfaces, on surfaces exposed to nighttime frost, in conditions of high nighttime humidity, or when rain is expected.

Protect the treated surface from water, rain, and snow during the first 24 hours after application.

Apply the product at temperatures between +5°C and +35°C. The substrate temperature must not exceed 35°C.

Do not apply on newly laid asphalt; allow at least 30 days of curing before application.

PRODUCT DATA SHEET

APPLICATION

The product is ready to use. Mix **WINCOURT TC** with a low-speed drill mixer before application. It can be applied using a roller, brush, or airless spray pump.

CONSUMPTION

200 g/m² in 2 coats.

COLORS

Red, blue, light blue, white, green.

PACKAGING

20 kg buckets.

STORAGE

The product has a shelf life of 12 months when stored in its original, unopened packaging in a dry and protected place. Protect from frost. Store at temperatures between +5°C and +35°C.

SAFETY INSTRUCTIONS

PRECAUTIONS

For safety information, the user must refer to the latest Safety Data Sheet (SDS), prepared in accordance with applicable regulations. The SDS contains detailed information on the physical, toxicological, and safety characteristics of the product.

DISPOSAL AND ENVIRONMENTAL PRECAUTIONS

Do not release the product or empty containers into the environment. For detailed disposal instructions, refer to the most recent Safety Data Sheet (SDS).

PRODUCT DATA SHEET

PRODUCT CHARACTERISTICS FOR PROFESSIONAL USE ONLY

CHARACTERISTIC	STANDARD	RESULT
Appearance	-	Fluid paste
Color	-	Green, Light Blue, Blue, White, Red
Density at 20°C	EN ISO 2811-1	1,25 ± 0,05 kg/l
Dry solids content (by weight)	EN ISO 3251	50 ± 2%
Brookfield viscosity at 20°C	UNI EN 8490	8000 ± 2500 cPs

DISCLAIMER AND LEGAL NOTICE – WINKLER

The information and instructions contained in this Technical Data Sheet are prepared on the basis of WINKLER's best technical and application knowledge and are provided for guidance only. However, since WINKLER cannot directly control site conditions or the execution of works, these indications are in no way binding on WINKLER.

The data provided do not exempt the purchaser from the responsibility of verifying, through practical tests and comprehensive applications, the suitability of the product for the intended use and of determining whether it is appropriate for the desired application; the user assumes all responsibility arising from its use. The customer is also responsible for verifying that this Technical Data Sheet is valid for the batch of product of interest and that it has not been superseded by later editions. The updated Technical Data Sheet is available on WINKLER's official website.

The contents of this Technical Data Sheet may be reproduced in other project documents, but the resulting document may under no circumstances replace or supplement the Technical Data Sheet in force at the time of application of the WINKLER product. Any alteration of the text or conditions contained in this Technical Data Sheet or derived from it releases WINKLER from any liability. WINKLER reserves the right to make technical changes of any kind to its products and/or Technical Data Sheets without notice. This revision cancels and replaces all previous ones.