PRODUCT DATA SHEET

ITEM CODE: SEE DN
ISSUE DATE: 26/04/2026
REVIEW: NO. 2

ADEGUM LATEX

DESCRIPTION OF THE PRODUCT

FIELDS OF USE

ADEGUM LATEX is designed to prepare adhesive cement slurries for casting joints or to modify cement mixes, improving their workability, impermeability, and adhesion. It is suitable for restorations, repairs, plasters, smoothing compounds, swimming pools, dams, floors, wear-resistant slabs, ramps, and similar applications.

It can also be used as a bonding agent on concrete substrates prior to the application of **WINPLAN 370** and **WINPLAN PRO** screeds. In this case, the screeds must be applied using the “wet-on-wet” technique.

SURFACE PREPARATION

Thoroughly clean the substrate to remove dust, loose or friable material, and any foreign or non-adherent substances. Before applying the grout or cement mix, moisten the substrate until it is saturated but without surface water. Protect the treated surface for the first 24 hours from direct sunlight and wind, moistening if necessary.

RECOMMENDATIONS

Do not add any additives.
Do not use the product if the packaging is damaged.
Do not dilute with water or solvents.
Shake before use.

WARNINGS

Before applying the grout or cement mix, moisten the substrate until it no longer absorbs water. Protect it from direct sunlight and wind for the first 24 hours, moistening if necessary. Apply at temperatures between +5°C and +35.

APPLICATION

After thoroughly shaking the product in its container, add it to the mixing water.

Winkler Srl
Via M. Buonarroti, 15 - 20093 Cologno Monzese (Mi) - Italy
Tel. +39 02 26 700 605
info@winklerchimica.com - www.winklerchimica.com

CONSUMPTION
Liquid cement slurry: 2.5 parts cement, 1 part ADEGUMM LATEX, 1 part water
Rough cement slurry: 2.5 parts cement, 2 parts sand, 1 part ADEGUM LATEX, 1 part water
Mortars: 10% of the weight of the cement

PACKAGING
1 L bottles
5-10-20 L containers

STORAGE
The product in its original and undamaged packaging, can be stored for up to 12 months. Store at temperatures between +5°C and 35 °C. The product is not frost-resistant.

SAFETY INSTRUCTIONS

PRECAUTIONS
For safety information, the user must refer to the latest Safety Data Sheet (SDS), prepared in accordance with applicable regulations. The SDS contains detailed information on the physical, toxicological, and safety characteristics of the product.

DISPOSAL AND ENVIRONMENTAL PRECAUTIONS
Do not release the product or empty containers into the environment. For detailed disposal instructions, refer to the most recent Safety Data Sheet (SDS).

Winkler Srl
Via M. Buonarroti, 15 - 20093 Cologno Monzese (Mi) - Italy
Tel. +39 02 26 700 605
info@winklerchimica.com - www.winklerchimica.com

PRODUCT DATA SHEET

TECHNICAL FEATURES
(average value)

FEATURES	RESULTS
Appearance	Liquid
Colour	White
Density at +20°C	1.05 ± 0.02 g/cm^3
Reaction to fire (Euroclass)	F
Solid content	Approx. 28%
pH	9 ± 1
Elongation	1000%
Minimum film-forming temperature	+5°C

PRODUCT FOR PROFESSIONAL USE ONLY

DISCLAIMER AND LEGAL NOTICE – WINKLER

The information and instructions contained in this Technical Data Sheet are prepared on the basis of WINKLER's best technical and application knowledge and are provided for guidance only. However, since WINKLER cannot directly control site conditions or the execution of works, these indications are in no way binding on WINKLER.

The data provided do not exempt the purchaser from the responsibility of verifying, through practical tests and comprehensive applications, the suitability of the product for the intended use and of determining whether it is appropriate for the desired application; the user assumes all responsibility arising from its use. The customer is also responsible for verifying that this Technical Data Sheet is valid for the batch of product of interest and that it has not been superseded by later editions. The updated Technical Data Sheet is available on WINKLER's official website.

The contents of this Technical Data Sheet may be reproduced in other project documents, but the resulting document may under no circumstances replace or supplement the Technical Data Sheet in force at the time of application of the WINKLER product. Any alteration of the text or conditions contained in this Technical Data Sheet or derived from it releases WINKLER from any liability. WINKLER reserves the right to make technical changes of any kind to its products and/or Technical Data Sheets without notice. This revision cancels and replaces all previous ones.

winkler® Advanced Building Material

Winkler Srl
Via M. Buonarroti, 15 - 20093 Cologno Monzese (Mi) - Italy
Tel. +39 02 26 700 605
info@winklerchimica.com - www.winklerchimica.com